

CBD15-170J

Electric Walkie Pallet Truck

Advantages

Configuration and Performance

- The truck has compact structure and is economic.
- Permanent magnet drive motor assembled on the truck has simple structure and is easy for maintenance.
- Stepless speed regulating is easy for operation and maintenance.
- Open type layout of battery is easy for replacement.
- Built-in charger is standard configuration.
- Maintenance-free battery is safe and non-pollution.
- The truck is compact and suitable for narrow space operation.
- Special design for Fork in and out of double-faced pallet.
- Lifting automatic limit is safe and energy saving.
- Emergency reversing device and emergency brake switch are standard configuration.
- The truck has low noise and small energy consumption and only 2 kw/h energy is consumed daily.



HELI CBD15-170J

Feature		
Model		CBD15
Configuration No.		170J
Weight		1500
Load center	kg	600
Wheel base	mm	1285/1235
Operating type	mm	Walkie
Wheels		
Wheels type		PU
Wheel quantity		1/0/4
Driving wheel/Balance wheel /Bearing wheel		φ210×70
Driving wheel size	mm	φ84×70 (双)
Balance wheel size	mm	φ80×101 (单)
Bearing wheel size	mm	—
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Outside width between forks	mm	550/685
Inside width between forks	mm	390
Fork length	mm	1150/1200
Fork width	mm	160
Fork thickness	mm	73
Overall length	mm	1648/1698
Overall width	mm	570/685
Overall height(With handle)	mm	1213
Overall height(Without handle)	mm	634
Min.Turning radius	mm	1414/1464
Min.Aisle width for pallets 800×1200	mm	1728/1778
Min.Aisle width for pallets 1000×1200	mm	1764/1814
Performance		
Travel speed,laden/unladen	km/h	3.5/4
Lift speed,laden/unladen	mm/s	30/35
Lowering speed,laden/unladen	mm/s	35/30
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor	KW	DC0.65
Lift motor	KW	DC0.8
Steering motor	KW	—
Battery voltage / capacity	V/Ah	24/75(Standard)/85(Options)
Brake		Electromagnetic/regenerative
Controller		Standard configuration HELI/Optional configuration CURTIS 1212F
Weight		
Battery weight	kg	50
Service weight with battery	kg	210

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.

ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
 TEL : 63639068(America); 63639258(Europe); 63639358(Asia); 63662105(Africa & Middle East);
 63639530(Warehouse Equipment); 63639531(Wheel loader)
 FAX : (86 551)63639966
 WEBSITE : <http://www.helichina.net>
 Email : hel@helichina.net

AUTHORIZED DEALER



TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 25 YEARS